

27 August 2020

THICK MINERALISED MAFIC-ULTRAMAFIC UNIT INTERSECTED AT DEPTH BELOW INVESTIGATORS

48.7m thick mafic-ultramafic unit from 503m downhole has been intersected by MAD181 at Investigators:

- The interval includes a 10m thick ultramafic with disseminated and blebby nickel-copper sulphides (<5% sulphides with pentlandite (pn), chalcopyrite (cp) and pyrrhotite (py)) from 541m downhole
- The 48.7m thick fertile mafic-ultramafic unit intersected by MAD181 is preserved and has not been structurally modified, supporting the potential for the presence of nickel-copper sulphide deposits that are intact and unaltered
- MAD181 also intersected a second mineralised ultramafic from 282.6m to 288.6m with nickel-copper sulphides (<2% sulphides with pn, cy and po)

The first deep drill hole at Fairbridge has also intersected a mineralised ultramafic at depth:

- MAD183 at Fairbridge has intersected an 11.6m thick mafic-ultramafic unit with disseminated nickel-copper sulphides (<5% sulphides with pn, cy and po) from 359.3m downhole
- The mineralised ultramafic intersected in MAD181 and MAD183 is on the same east-west horizon and located down-dip of the significant massive nickel-copper sulphide mineralisation already discovered at shallow depths along the Cathedrals Belt

Diamond drilling continues 24/7:

- Two diamond rigs drilling 24/7 at Mt Alexander
- MAD181 is currently at 770m downhole with drilling continuing
- MAD183 was completed to 693.5m downhole, with the drill rig now commencing on MAD184 at Investigators to test a surface moving loop electromagnetic (MLEM) anomaly to the west of known high-grade nickel-copper sulphides

New DHEM surveys underway:

- The DHEM survey crew arrived at site yesterday and will survey MAD180, MAD181, MAD182 and MAD183 with data acquisition expected to take two days per drill hole
- Geophysical modelling and interpretation to follow, with further drill holes to be planned once results of the DHEM surveys are reviewed

Growth focused Western Australian nickel company St George Mining Limited (ASX: **SGQ**) (“**St George**” or “**the Company**”) is pleased to announce that drilling has intersected thick mafic-ultramafic units with nickel-copper sulphide mineralisation at its flagship Mt Alexander Project, located in the north-eastern Goldfields.

NICKEL-COPPER SULPHIDES DISCOVERED AT DEPTH

Two drill holes – MAD181 at Investigators and MAD183 at Fairbridge – have delivered significant exploration success with both drill holes intersecting mineralised mafic-ultramafic units at depth.

All high-grade nickel-copper sulphides discovered along the Cathedrals Belt to date are hosted in mafic-ultramafic intrusives. The identification of further thick intrusives at depth increases confidence that additional significant nickel-copper sulphide mineralisation is present within the extensive Cathedrals Belt intrusive mineral system.

The results in MAD181 and MAD183 further validate our geological model that interprets the mineralised Cathedrals Belt commencing near surface and dipping to the north-northwest at an angle of approximately 40 degrees. Both drill holes intersected the same mafic-ultramafic intrusive unit along the target horizon.

The continuity of nickel-copper sulphide mineralisation along this structural zone is now established for more than 600m in the down-dip direction. This supports the potential for further high-grade nickel-copper sulphide mineralisation along the structure – both up-dip and down-dip from the mineralisation intersected in MAD181 and MAD183, and also along strike to the east and west.

Figure 1 illustrates the large target horizon for nickel-copper sulphides as well as the location of the latest discoveries in MAD181 and MAD183. The target horizon is interpreted to continue in an east-west orientation with a prospective strike of more than 4km from Investigators in the west to Radar in the east.




Figure 1 – Schematic orthographic view of the Cathedrals Belt showing the large interpreted target horizon, the new discoveries in MAD181 and MAD183 as well as existing drilling and known massive nickel-copper sulphides.

John Prineas, St George Mining’s Executive Chairman, said:

“The first two deep drill holes in the current campaign – MAD180 at Investigators and MAD182 at Cathedrals – successfully intersected intrusive-style rocks and confirmed the presence of prospective geology at depth.

“The next two holes – MAD181 at Investigators and MAD183 at Fairbridge – have provided another huge leap forward with thick intersections of mineralised mafic-ultramafic units.

“A very important aspect of this discovery is the preserved nature of the 48m thick unit intersected at Investigators. This significantly increases the potential likelihood for the presence of larger accumulations of nickel-copper mineralisation nearby.

“We are continuing our aggressive exploration programme, with downhole EM surveys underway and two diamond rigs drilling 24/7 to test more exciting nickel-copper sulphide targets.”

MAD181:

MAD181 is currently drilled to 770m downhole. Drilling is continuing to a planned depth of 800m.

Geological logging of the drill hole is set out below.

MAD181	Geological log of rock types
0 to 40.5m	<i>Cover and granite saprolite</i>
40.5m to 214m	<i>Granites including with cross-cutting pegmatites.</i>
214m to 282.6m	<i>Grano-diorite, minor cross-cutting pegmatites.</i>
282.6 to 288.6m	<i>Ultramafic with trace disseminated sulphides. <2% sulphides comprising pentlandite (pn), chalcopyrite (cp) and pyrrhotite (po).</i>
288.6m to 401m	<i>Grano-diorite, minor cross-cutting pegmatites.</i>
410m to 503.1m	<i>Granites including with cross-cutting pegmatites. Potassic alteration throughout. Increasing structural complexity toward base.</i>
503.1m to 541.9m	<i>Mafic intrusive with large granitic xenoliths. <40mm granite xenoliths within upper mafic unit. Gradational contact with below ultramafic.</i>
541.9m to 551.8m	<i>Ultramafic intrusive with disseminated sulphides. <5% sulphides comprising pentlandite (pn), chalcopyrite (cp) and pyrrhotite (po) increasing in abundance towards basal contact.</i>
551.8m to 588.1m	<i>Granites including with cross-cutting pegmatites.</i>
588.1m to 590.2m	<i>Mafic dolerite. Brecciated with associated strong silica-chlorite alteration +/- sulphides pyrite (py) and chalcopyrite (cp).</i>
590.2m to 728.5m	<i>Grano-diorite, cross-cutting pegmatites.</i>
728.5m to 770m	<i>Granites including with cross-cutting pegmatites.</i>

So far, MAD181 has intersected two significant intervals of ultramafic with nickel-copper sulphide mineralisation – between 282.6m to 288.6m and from 541.9m to 551.8m. The latter interval is within a 48.7m thick intrusive from 503.1m downhole.

Minor chalcopyrite and pyrite sulphides were also intersected between 588.1m to 590.2m downhole within an intrusive mafic dolerite – providing further evidence of the large intrusive system at the Cathedrals Belt.

The 48.7m thick mafic-ultramafic unit intersected from 503.1m downhole is preserved with no sign of structural modification; see photograph in Figure 2.

The discovery of this unit has important implications for the prospectivity of the target area around the hole.

Firstly, the thickness of the unit supports the potential for large volumes of intrusive rocks at depth along the Cathedrals Belt.

Secondly, the preserved nature of the unit supports the potential for any nickel-copper sulphides within the unit to remain unaltered and intact.




Figure 2 - Photo of drill core from MAD181. The core tray contains the interval between 539m to 551m. The core highlighted on the right is from 547.5m downhole and shows disseminated and blebby nickel-copper sulphides. (codes: UX\$ = ultramafic with sulphides; UXT\$ = ultramafic with textured sulphides; UX = ultramafic; MdP = mafic intrusive)

Figure 3 is a schematic section of MAD181 and shows the significant down-dip continuity from the shallow high-grade mineralisation at Investigators. This Figure highlights the more than 500m of prospective and untested area that is up-dip of MAD181.




Figure 3 – Schematic section along 231600E (+/- 100m) showing existing drilling and interpreted geology.

MAD183:

MAD183 was completed to a downhole depth of 693.5m at Fairbridge. Geological logging is set out below.

MAD183	Geological log of rock types
0 to 12m	<i>Cover and granite saprolite</i>
12m to 201.7m	<i>Granites including cross-cutting pegmatites</i>
201.7m to 208.6m	<i>Differentiated mafic intrusive. Granitic xenoliths above mafic with carbonate veining throughout. No sulphides observed.</i>
208.6m to 340.6m	<i>Granites with mafic band at 259m to 259.4m.</i>
340.6m to 353.7m	<i>Predominantly pegmatites cross-cutting granite. Likely indicating structural pre-existing structural corridor.</i>
353.7m to 359.3m	<i>Mafic intrusive with large granitic xenoliths. <40mm granite xenoliths within upper mafic unit. Gradational contact with below ultramafic.</i>
359.3m to 365.3m	<i>Ultramafic intrusive with disseminated sulphides. <5% sulphides comprising pentlandite (pn), chalcopyrite (cp) and pyrrhotite (po) increasing in abundance towards basal contact.</i>
365.3m to 392m	<i>Granites including minor cross-cutting pegmatites</i>
392m to 589m	<i>Grano-diorite, minor cross-cutting pegmatites.</i>
589m to 693.5m	<i>Granites including minor cross-cutting pegmatites</i>

Ultramafic with nickel-copper sulphides was intersected between 359.3m to 365.3m. This mineralised ultramafic is part of a broader mafic-ultramafic unit and has been intersected by MAD183 in the same east-west horizon as the mineralised ultramafic intersected by MAD181 (541.9 to 551.8m). The distance between these holes is approximately 1,400m, indicating a very significant strike of the mineralised intrusive rocks across the Cathedrals Belt.

Numerous nickel-copper sulphide gossans have been observed at Fairbridge. The intersection of a mineralised ultramafic in MAD183 supports the potential for the gossans to constitute the surface expression of a nickel sulphide deposit below surface.

Similar gossans drilled at the Stricklands and Cathedrals Prospects have been confirmed as associated with proximal massive nickel-copper sulphide sources.

DHEM SURVEYS FOR DEEP DRILL HOLES

DHEM surveys for the latest deep drill holes commenced today. The first hole to be surveyed is MAD183, with MAD181, MAD180 and MAD182 to follow.

The full depth extent of each hole will be surveyed. Data will be generally be acquired at 10m intervals with 5m intervals for priority areas where mineralisation and intrusive rocks have been intersected. Further infill surveying may be completed subject to initial results.

The survey for each hole is expected to take two days.

DRILL PROGRAMME

MAD184 is currently being drilled to test a SQUID MLEM anomaly that was generated during the last surface EM programme. The drill hole has been designed to a depth of 450m.

While the MLEM anomaly is only visible in the Y and Z data, it is ranked highly as it is located along strike from known nickel-copper sulphides, and similar to the anomaly tested by MAD179.

MAD185 will follow MAD181 and has been planned at Investigators to test the strong off-hole conductor identified from the DHEM survey in MAD179. The conductivity/thickness of the conductor is modelled as 21,500 Siemens and is consistent with massive sulphides.

MAD185 is planned to a depth of 450m, with the target modelled to be intersected at 400m downhole.

Table 1 below contains drill hole details for the holes in the current campaign to test new targets, including the holes currently being drilled.

Hole ID	Prospect	East	North	RL	Depth	Azi	Dip
MAD179	Investigators	230928	6806709	418	351.9	180	-70
MAD180	Investigators	231439	6807031	423	850	180	-70
MAD180W1	Investigators	231442.0	6806869.6	-71.6	877.4	180	-68
MAD181	Investigators	231726	6807301	425	800	180	-65
MAD182	Cathedrals	233960	6807824	412	750	170	-65
MAD183	Fairbridge	233095.0	6807173.3	415.0	750	180	-65
MAD184	Investigators	230606	6806836	415	450	180	-75
MAD185	Investigators	230930	6806711	418	350	157	-72

Table 1 – Drill hole details for diamond holes to test new targets.




Figure 4 – Plan view of the Cathedrals Belt showing areas of completed and planned drilling, overlaying interpreted geology and magnetics (TMI RTP 1VD).

COVID-19:

St George is managing its operations in compliance with COVID-19 regulations issued by State and Commonwealth authorities. We will continue to proactively manage drilling and other field programmes to protect the health and safety of our team and service providers.

About the Mt Alexander Project:

The Mt Alexander Project is located 120km south-southwest of the Agnew-Wiluna Belt, which hosts numerous world-class nickel deposits. The Project comprises six granted exploration licences – E29/638, E29/548, E29/962, E29/954, E29/972 and E29/1041.

The Cathedrals, Stricklands, Investigators and Radar nickel-copper-cobalt-PGE discoveries are located on E29/638, which is held in joint venture by St George Mining Limited (75%) and Western Areas Limited (25%). St George is the Manager of the Project, with Western Areas retaining a 25% non-contributing interest in the Project (in regard to E29/638 only) until there is a decision to mine.

Authorised for release by the Board of St George Mining Limited.

For further information, please contact:

John Prineas
Executive Chairman
St George Mining Limited
+61 411 421 253
john.prineas@stgm.com.au

Peter Klinger
Media and Investor Relations
Cannings Purple
+61 411 251 540
pklinger@canningspurple.com.au

Competent Person Statement:

The information in this report that relates to Exploration Targets, Exploration Results, Mineral Resources or Ore Reserves is based on information compiled by Mr Dave O'Neill, a Competent Person who is a Member of The Australasian Institute of Mining and Metallurgy. Mr O'Neill is employed by St George Mining Limited to provide technical advice on mineral projects, and he holds performance rights issued by the Company.

Mr O'Neill has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr O'Neill consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The following section is provided for compliance with requirements for the reporting of exploration results under the JORC Code, 2012 Edition.

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections)

Criteria	JORC Code explanation	Commentary
<p>Sampling techniques</p>	<p><i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i></p>	<p>Drilling programmes are completed by Reverse Circulation (RC) and Diamond Core drilling. Surface MT/AMT surveys were completed by Moombarriga Geophysics.</p> <p><i>Diamond Core Sampling:</i> The sections of the core that are selected for assaying are marked up and then recorded on a sample sheet for cutting and sampling at the certified assay laboratory. Samples of HQ or NQ2 core are cut just to the right of the orientation line where available using a diamond core saw, with half core sampled lengthways for assay.</p> <p><i>RC Sampling:</i> All samples from the RC drilling are taken as 1m samples for laboratory assay.</p> <p><i>MT/AMT Surveying:</i> The surveys were conducted using the Phoenix MTU system and Metronix ADU07e system. The sensors were recorded at 500m intervals with 100m infill over the Investigators Prospect.</p> <p>Two survey lines were recorded, one N-S and one E-W line. The N-S line was centred on the Investigators Prospect and included the 100m infill AMT stations, while the E-W line was completed approx. 500m to the north of the Cathedrals belt to image the stratigraphy down dip of the known nickel-copper deposits.</p> <p>Appropriate QAQC samples (standards, blanks and duplicates) are inserted into the sequences as per industry best practice. Samples are collected using cone or riffle splitter. Geological logging of RC chips is completed at site with representative chips being stored in drill chip trays.</p>
	<p><i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i></p>	<p><i>RC Sampling:</i> Samples are taken on a one metre basis and collected using uniquely numbered calico bags. The remaining material for that metre is collected and stored in a green plastic bag marked with that specific metre interval. The cyclone is cleaned with compressed air after each plastic and calico sample bag is removed. If wet sample or clays are encountered then the cyclone is opened and cleaned manually and with the aid of a compressed air gun. A blank sample is inserted at the beginning of each hole, and a duplicate sample is taken every 50th sample. A certified sample standard is also added according to geology, but at no more than 1:50 samples.</p> <p>Geological logging of RC chips is completed at site with representative chips being stored in drill chip trays. Downhole surveys of dip and azimuth are conducted using a single shot camera every 30m, and using a downhole Gyro when required, to detect deviations of the hole from the planned dip and azimuth. The drill-hole collar locations are recorded using a hand-held GPS, which has an accuracy of +/- 5m. All drill-hole collars will be surveyed to a greater degree of accuracy using a certified surveyor at a later date.</p> <p><i>Diamond Core Sampling:</i> For diamond core samples, certified sample standards were added as every 25th sample. Core recovery calculations are made through a reconciliation of the actual core and the driller's records. Downhole surveys of dip and azimuth were conducted using a single shot camera every 30m to detect deviations of the hole from the planned dip and azimuth. The drill-hole collar locations are recorded using a hand-held GPS, which has an accuracy of +/- 5m.</p>

Criteria	JORC Code explanation	Commentary
	<p><i>Aspects of the determination of mineralisation that are Material to the Public Report.</i></p> <p><i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i></p>	<p><i>RC Sampling:</i> A 1m composite sample is taken from the bulk sample of RC chips that may weigh in excess of 40 kg. Each sample collected for assay typically weighs 2-3kg, and once dried, is prepared for the laboratory as per the Diamond samples below.</p> <p><i>Diamond Core Sampling:</i> Diamond core (both HQ and NQ2) is half-core sampled to geological boundaries no more than 1.5m and no less than 10cm. Samples less than 3kg are crushed to 10mm, dried and then pulverised to 75µm. Samples greater than 3kg are first crushed to 10mm then finely crushed to 3mm and input into the rotary splitters to produce a consistent output weight for pulverisation.</p> <p>Pulverisation produces a 40g charge for fire assay. Elements determined from fire assay are gold (Au), platinum (Pt) and palladium (Pd) with a 1ppb detection limit. To determine other PGE concentrations (Rh, Ru, Os, Ir) a 25g charge for nickel sulphide collect fire assay is used with a 1ppb detection limit.</p> <p>Other elements will be analysed using an acid digest and an ICP finish. These elements are: Ag, Al, As, Bi, Ca, Cd, Co, Cr, Fe, K, Li, Mg, Mn, Mo, Nb, Ni, P, Pb, S, Sb, Sn, Te, Ti, V, W, Zn. The sample is digested with nitric, hydrochloric, hydrofluoric and perchloric acids to effect as near to total solubility of the sample as possible. The sample is then analysed using ICP-AES or ICP-MS.</p> <p>LOI (Loss on Ignition) will be completed on selected samples to determine the percentage of volatiles released during heating of samples to 1000°C.</p>
<p>Drilling techniques</p>	<p><i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i></p>	<p><i>Diamond Core Sampling:</i> The collars of the diamond holes were drilled using RC drilling down through the regolith to the point of refusal or to a level considered geologically significant to change to core. The hole was then continued using HQ diamond core until the drillers determined that a change to NQ2 coring was required.</p> <p>The core is oriented and marked by the drillers. The core is oriented using ACT Mk II electric core orientation.</p> <p><i>RC Sampling:</i> The RC drilling uses a 140 mm diameter face hammer tool. High capacity air compressors on the drill rig are used to ensure a continuously sealed and high pressure system during drilling to maximise the recovery of the drill cuttings, and to ensure chips remain dry to the maximum extent possible.</p>
<p>Drill sample recovery</p>	<p><i>Method of recording and assessing core and chip sample recoveries and results assessed.</i></p> <p><i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i></p>	<p><i>Diamond Core Sampling:</i> Diamond core recoveries are recorded during drilling and reconciled during the core processing and geological logging. The core length recovered is measured for each run and recorded which is used to calculate core recovery as a percentage.</p> <p><i>RC Sampling:</i> RC samples are visually checked for recovery, moisture and contamination. Geological logging is completed at site with representative RC chips stored in chip trays.</p> <p><i>RC Sampling:</i> Samples are collected using cone or riffle splitter. Geological logging of RC chips is completed at site with representative chips being stored in drill chip trays.</p> <p><i>Diamond Core Sampling:</i> Measures taken to maximise core recovery include using appropriate core diameter and shorter barrel length through the weathered zone, which at Cathedrals and Investigators is mostly <20m and Stricklands <40m depth. Primary locations for core loss in fresh rock are on geological contacts and structural zones, and drill techniques are adjusted accordingly, and if possible these zones are predicted from the geological modelling.</p>

Criteria	JORC Code explanation	Commentary
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	To date, no sample recovery issues have yet been identified that would impact on potential sample bias in the competent fresh rocks that host the mineralised sulphide intervals.
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	Geological logging is carried out on all drill holes with lithology, alteration, mineralisation, structure and veining recorded.
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	Logging of diamond core and RC samples records lithology, mineralogy, mineralisation, structures (core only), weathering, colour and other noticeable features. Core was photographed in both dry and wet form.
	<i>The total length and percentage of the relevant intersections logged.</i>	All drill holes are geologically logged in full and detailed litho-geochemical information is collected by the field XRF unit. The data relating to the elements analysed is used to determine further information regarding the detailed rock composition.
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	<i>Diamond Core Sampling:</i> Diamond core was drilled with HQ and NQ2 size and sampled as complete half core to produce a bulk sample for analysis. Intervals selected varied from 0.3 – 1m (maximum) The HQ and NQ2 core is cut in half length ways just to the right of the orientation line where available using a diamond core saw. All samples are collected from the same side of the core where practicable. Assay preparation procedures ensure the entire sample is pulverised to 75 microns before the sub-sample is taken. This removes the potential for the significant sub-sampling bias that can be introduced at this stage.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	RC samples are collected in dry form. Samples are collected using cone or riffle splitter when available. Geological logging of RC chips is completed at site with representative chips being stored in drill chip trays.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	<i>RC Sampling:</i> Sample preparation for RC chips follows a standard protocol. The entire sample is pulverised to 75µm using LM5 pulverising mills. Samples are dried, crushed and pulverized to produce a homogenous representative sub-sample for analysis. A grind quality target of 90% passing 75µm is used.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	Quality control procedures include submission of Certified Reference Materials (standards), duplicates and blanks with each sample batch. QAQC results are routinely reviewed to identify and resolve any issues. <i>RC Sampling:</i> Field QC procedures maximise representivity of RC samples and involve the use of certified reference material as assay standards, along with blanks, duplicates and barren washes. <i>Diamond Core Sampling:</i> Drill core is cut in half lengthways and the total half-core submitted as the sample. This meets industry standards where 50% of the total sample taken from the diamond core is submitted.

Criteria	JORC Code explanation	Commentary
	<p><i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i></p>	<p>Duplicate samples are selected during sampling. Samples comprise two quarter core samples for Diamond Core. Duplicate RC samples are captured using two separate sampling apertures on the splitter.</p>
	<p><i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i></p>	<p>The sample sizes are considered to be appropriate to correctly represent base metal sulphide mineralisation and associated geology based on: the style of mineralisation (massive and disseminated sulphides), the thickness and consistency of the intersections and the sampling methodology.</p>
<p>Quality of assay data and laboratory tests</p>	<p><i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i></p>	<p>For RC sampling, a 30 gram sample will be fire assayed for gold, platinum and palladium. The detection range for gold is 1 – 2000 ppbAu, and 0.5 – 2000 ppb for platinum and palladium. This is believed to be an appropriate detection level for the levels of these elements within this specific mineral environment. However, should Au, Pt or Pd levels reported exceed these levels; an alternative assay method will be selected.</p> <p>All other metals will be analysed using an acid digest and an ICP finish. The sample is digested with nitric, hydrochloric, hydrofluoric and perchloric acids to effect as near to total solubility of the sample as possible. The solution containing samples of interest, including those that need further review, will then be presented to an ICP-OES for the further quantification of the selected elements.</p> <p>Diamond core samples are analysed for Au, Pt and Pd using a 40g lead collection fire assay; for Rh, Ru, Os, Ir using a 25g nickel sulphide collection fire assay; and for Ag, Al, As, Bi, Ca, Cd, Co, Cr, Fe, K, Li, Mg, Mn, Mo, Nb, Ni, P, Pb, S, Sb, Sn, Te, Ti, V, W, Zn using a four acid digest and ICP-AES or MS finish. The assay method and detection limits are appropriate for analysis of the elements required.</p>
	<p><i>For geophysical tools, spectrometres, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i></p>	<p>MT/AMT: The surveys were conducted using the Phoenix MTU system and Metronix ADU07e system. The sensors were recorded at 500m intervals with 100m infill over the Investigators Prospect.</p> <p>XRF: A handheld XRF instrument (Olympus Innov-X Spectrum Analyser) is used to systematically analyse the drill core and RC sample piles onsite. One reading is taken per metre, however for any core samples with matrix or massive sulphide mineralisation then multiple samples are taken at set intervals per metre. The instruments are serviced and calibrated at least once a year. Field calibration of the XRF instrument using standards is periodically performed (usually daily).</p> <p>The handheld XRF results are only used for preliminary assessment and reporting of element compositions, prior to the receipt of assay results from the certified laboratory.</p>
	<p><i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i></p>	<p>Laboratory QAQC involves the use of internal lab standards using certified reference material (CRMs), blanks and pulp duplicates as part of in-house procedures. The Company also submits a suite of CRMs, blanks and selects appropriate samples for duplicates.</p> <p>Sample preparation checks for fineness are performed by the laboratory to ensure the grind size of 90% passing 75µm is being attained.</p>
<p>Verification of sampling and assaying</p>	<p><i>The verification of significant intersections by either independent or alternative company personnel.</i></p>	<p>Significant intersections are verified by the Company's technical staff.</p>
	<p><i>The use of twinned holes.</i></p>	<p>No twinned holes have been planned for the current drill programme.</p>

Criteria	JORC Code explanation	Commentary
	<p><i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i></p> <hr/> <p><i>Discuss any adjustment to assay data.</i></p>	<p>Primary data is captured onto a laptop using acQuire software and includes geological logging, sample data and QA/QC information. This data, together with the assay data, is entered into the St George Mining central SQL database which is managed by external consultants.</p> <hr/> <p>No adjustments or calibrations will be made to any primary assay data collected for the purpose of reporting assay grades and mineralised intervals. For the geological analysis, standards and recognised factors may be used to calculate the oxide form assayed elements, or to calculate volatile free mineral levels in rocks.</p>
Location of data points	<p><i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i></p> <hr/> <p><i>Specification of the grid system used.</i></p> <hr/> <p><i>Quality and adequacy of topographic control.</i></p>	<p>Drill holes and MT/AMT stations have been located and pegged using a DGPS system with an expected accuracy of +/-5m for easting, northing and elevation.</p> <p>Downhole surveys are conducted using a single shot camera approximately every 30m or downhole Gyro during drilling to record and monitor deviations of the hole from the planned dip and azimuth. Post-drilling downhole gyroscopic surveys will be conducted, which provide more accurate survey results.</p> <hr/> <p>The grid system used is GDA94, MGA Zone 51.</p> <hr/> <p>Elevation data has been acquired using DGPS surveying at individual collar locations and entered into the central database. A topographic surface has been created using this elevation data.</p>
Data spacing and distribution	<p><i>Data spacing for reporting of Exploration Results.</i></p> <hr/> <p><i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i></p> <hr/> <p><i>Whether sample compositing has been applied.</i></p>	<p>The spacing and distribution of holes is not relevant to the drilling programs which are at the exploration stage rather than definition drilling.</p> <hr/> <p>The completed drilling at the Project is not sufficient to establish the degree of geological and grade continuity to support the definition of Mineral Resource and Reserves and the classifications applied under the 2012 JORC code.</p> <hr/> <p>No compositing has been applied to the exploration results.</p>
Orientation of data in relation to geological structure	<p><i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i></p> <hr/> <p><i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i></p>	<p>The drill holes are drilled to intersect the modelled mineralised zones at a near perpendicular orientation (unless otherwise stated). However, the orientation of key structures may be locally variable and any relationship to mineralisation has yet to be identified.</p> <hr/> <p>No orientation based sampling bias has been identified in the data to date.</p>
Sample security	<p><i>The measures taken to ensure sample security.</i></p>	<p>Chain of Custody is managed by the Company until samples pass to a duly certified assay laboratory for subsampling and assaying. The RC sample bags are stored on secure sites and delivered to the assay laboratory by the Company or a competent agent. When in transit, they are kept in locked premises. Transport logs have been set up to track the progress of samples.</p>
Audits or reviews	<p><i>The results of any audits or reviews of sampling techniques and data.</i></p>	<p>Sampling techniques and procedures are regularly reviewed internally, as is data. To date, no external audits have been completed on the drilling programme.</p>

Section 2 Reporting of Exploration Results (Criteria listed in section 1 will also apply to this section where relevant)

Criteria	JORC Code explanation	Commentary
Mineral Tenement and Land Status	<p>Type, name/reference number, location and ownership including agreements or material issues with third parties including joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</p> <p>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</p>	<p>The Mt Alexander Project is comprised of five granted Exploration Licences (E29/638, E29/548, E29/954, E29/962 and E29/972). Tenement E29/638 is held in Joint Venture between St George (75% interest) and Western Areas (25% interest). E29/638 and E29/548 are also subject to a royalty in favour of a third party that is outlined in the ASX Release dated 17 December 2015 (as regards E29/638) and the ASX release dated 18 September 2015 (as regards E29/548).</p> <p>No environmentally sensitive sites have been identified on the tenements. A registered Heritage site known as Willsmore 1 (DAA identification 3087) straddles tenements E29/548 and E29/638. All five tenements are in good standing with no known impediments.</p>
Exploration Done by Other Parties	<p>Acknowledgment and appraisal of exploration by other parties.</p>	<p>Exploration on tenements E29/638 and E29/962 has been largely for komatiite-hosted nickel sulphides in the Mt Alexander Greenstone Belt. Exploration in the northern section of E29/638 (Cathedrals Belt) and also limited exploration on E29/548 has been for mafic/ultramafic intrusion related Ni-Cu-PGE sulphides. No historic exploration has been identified on E29/954 or E29/972.</p> <p>High grade nickel-copper-PGE sulphides were discovered at the Mt Alexander Project in 2008. Drilling was completed to test co-incident electromagnetic (EM) and magnetic anomalies associated with nickel-PGE enriched gossans in the northern section of current tenement E29/638. The drilling identified high grade nickel-copper mineralisation in granite-hosted ultramafic units and the discovery was named the Cathedrals Prospect.</p>
Geology	<p>Deposit type, geological setting and style of mineralisation</p>	<p>The Mt Alexander Project is at the northern end of a western bifurcation of the Mt Ida Greenstones. The greenstones are bound to the west by the Ida Fault, a significant Craton-scale structure that marks the boundary between the Kalgoorlie Terrane (and Eastern Goldfields Superterrane) to the east and the Youanmi Terrane to the west.</p> <p>The Mt Alexander Project is prospective for further high-grade komatiite-hosted nickel-copper-PGE mineralisation (both greenstone and granite hosted) and also precious metal mineralisation (i.e. orogenic gold) that is typified elsewhere in the Yilgarn Craton.</p>
Drill hole information	<p>A summary of all information material to the understanding of the exploration results including tabulation of the following information for all Material drill holes:</p> <ul style="list-style-type: none"> • Easting and northing of the drill hole collar • Elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar • Dip and azimuth of the hole • Down hole length and interception depth • Hole length 	<p>Drill hole collar locations are shown in the maps and tables included in the body of the relevant ASX releases.</p>
Data aggregation methods	<p>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</p>	<p>Reported assay intersections are length and density weighted. Significant intersections are determined using both qualitative (i.e. geological logging) and quantitative (i.e. lower cut-off) methods.</p> <p>For massive sulphide intersections, the nominal lower cut-off is 2% for either nickel or copper. For disseminated, blebby and matrix sulphide intersections the nominal lower cut-off for nickel is 0.3%.</p>

Criteria	JORC Code explanation	Commentary
	<p><i>Where aggregated intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></p> <hr/> <p><i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i></p>	<p>Any high-grade sulphide intervals internal to broader zones of sulphide mineralisation are reported as included intervals.</p> <p>Any disseminated, matrix, brecciated or stringer sulphides with (usually) >1% nickel or copper on contact with massive sulphide mineralisation are grouped with the massive sulphides for calculating significant intersections and the massive sulphide mineralisation is reported as an including intersection.</p> <hr/> <p>No metal equivalent values are used for reporting exploration results.</p>
Relationship between mineralisation widths and intercept lengths	<p><i>These relationships are particularly important in the reporting of exploration results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect.</i></p>	<p>Assay intersections are reported as down hole lengths. Drill holes are planned as perpendicular as possible to intersect the target EM plates and geological targets so downhole lengths are usually interpreted to be near true width.</p>
Diagrams	<p><i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plane view of drill hole collar locations and appropriate sectional views.</i></p>	<p>A prospect location map, cross section and long section are shown in the body of relevant ASX Releases.</p>
Balanced Reporting	<p><i>Where comprehensive reporting of all Exploration Results is not practical, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i></p>	<p>Reports on recent exploration can be found in ASX Releases that are available on our website at www.stgm.com.au:</p> <p>The exploration results reported are representative of the mineralisation style with grades and/or widths reported in a consistent manner.</p>
Other substantive exploration data	<p><i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observation; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i></p>	<p>All material or meaningful data collected has been reported.</p>
Further Work	<p><i>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large – scale step – out drilling).Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i></p>	<p>A discussion of further exploration work underway is contained in the body of recent ASX Releases.</p> <p>Further exploration will be planned based on ongoing drill results, geophysical surveys and geological assessment of prospectivity.</p>