

3 October 2018

DOWNHOLE EM SURVEYS LIGHT UP STRONG CONDUCTORS AT INVESTIGATORS PROSPECT

HIGHLIGHTS:

- **Downhole electromagnetic (DHEM) surveys in the recently completed drill holes at Investigators have identified strong off-hole conductors that are consistent with a massive sulphide source**
- **Surveys in MAD116 and MAD118 result in the re-interpretation of conductor MAD111:X1 as three strong conductive sources with three new targets modelled for drilling:**
 - **Conductor MAD116:X1 with conductivity of 208,000 Siemens and located to the north of MAD116 and MAD118**
 - **Conductor MAD116:X2 with conductivity of 188,000 Siemens and located to the south of MAD116 and MAD118**
 - **Conductor MAD116:XXX with conductivity of 250,000 Siemens and located in a possible shear zone between MAD116 and MAD118**
- **Survey in MAD120b identifies a strong off-hole conductor, named MAD120b:X1, trending in a westerly down-dip direction with modelled conductivity of 210,000 Siemens**
- **The new conductors are located down plunge of the previously intersected mineralised ultramafic on the MAD111 section indicating the potential for a significant extension to the known mineralisation at Investigators**
- **Drilling of the new conductors is scheduled to commence later this week**
- **DHEM surveys of other recently completed drill holes is continuing**

Emerging Western Australian nickel company St George Mining Limited (ASX: **SGQ**) (“**St George**” or “**the Company**”) is pleased to announce exciting results from the DHEM surveys carried out in a number of the recently completed drill holes at the Mt Alexander Project, located near Leonora in the north-eastern Goldfields.

John Prineas, St George Mining’s Executive Chairman, said:

“The DHEM surveys at Investigators are lighting up powerful conductors that are excellent targets for locating additional high-grade massive nickel-copper sulphide mineralisation.

“Drill holes MAD116, MAD118 and MAD120b were completed to test various positions along conductor MAD111:X1 at the Investigators Prospect, which was modelled with a strike extent of 80m and conductivity of 140,000 Siemens.

“Each of these holes intersected ultramafic rocks and nickel sulphides but not the kind of massive sulphides that could explain the strong EM conductor MAD111:X1.

“The new DHEM data has provided a breakthrough with modelling of the data indicating three strong conductors proximal to MAD116 and MAD118, and a large, strong conductor dipping to the west of MAD120b.

“The presence of multiple conductors suggests a large mineral system with potential to deliver a very significant increase in the down plunge strike of high-grade mineralisation on the MAD111 section.

“Drilling of these new targets will commence immediately after completion of the current hole MAD122, which is being completed approximately 260m to the west of these new conductors.”

DHEM SURVEYS PROVIDE BREAKTHROUGH

The DHEM survey data from each of MAD116 and MAD118 identified two strong off-hole EM conductors, one to the south of the drill holes and a larger conductor to the north of the drill holes.

The combined modelling of the data from both drill holes resulted in similar off-hole conductors to that from the individual model, giving a high level of confidence to the quality of the DHEM data and the modelling of the new EM plates. These two conductors – MAD116:X1 and MAD116:X2 – have properties consistent with massive sulphides.

A third conductive source was detected from the data in MAD116, with the source situated between MAD116 and MAD118. This conductor, MAD116:XXX, is interpreted to be steep dipping to the east or sub-vertical, and is probably sourced by massive sulphides along a structure such as a fault or shear. This is consistent with the mineralisation intersected in MAD118 which included a high-angle ribbon of massive nickel-copper sulphides, suggesting a structural influence on the massive sulphides in this location.




Figure 1 - MAD116 and MAD118 DHEM late time profiles of CH34 to CH39 (125ms to 371ms). Red profiles are modelled responses and black profiles are observed data. The sharp negative to positive cross-overs on the radial component (Bu, Bv) suggest a strong and proximal off-hole conductor.

Drill hole MAD120b was drilled to test the northern extent of conductor MAD111:X1. The hole was completed to a downhole depth of 240m with the target EM plate modelled at 190m downhole. Ultramafic with rare and trace sulphides was intersected between 191.26m to 193.85m downhole, with the remainder of the hole intersecting granites.

The DHEM survey in MAD120b detected a strong off-hole conductor to the south of the hole, and trending towards the west consistent with the down-dip direction. The modelled conductor MAD120b:X1 fits well with the observed DHEM response in MAD120b but is not a good fit with the data observed in the nearby MAD118. That suggests more complex geometry for the MAD120b:X1 conductor than a simple thin rectangular plate model.

Figure 2 below is an oblique view of the new modelled EM plates. Intersection of sulphide mineralisation where the plates are located will extend the down plunge mineralisation on this section some 100m.




Figure 2 - Oblique view, looking up (+20 degrees) towards 225° +/-25m showing new DHEM plates. Planned drill holes are in yellow. Other drill holes shown (green and white) did not intersect the target plates (brown).

The clear and strong conductive responses in the most recent DHEM surveys suggest good quality data obtained from highly conductive material, and provides confidence to the interpretation that the responses are from a massive sulphide source.

Table 1 shows key properties of the new DHEM plates at Investigators. In light of the multiple conductive sources at Investigators, and likely complex geometry of the source, further refinement of these targets will be made as they are drilled and additional data becomes available.

The interpretation of the DHEM plates as massive sulphides is considered robust, but they are unlikely to be definitive of any potential sulphide mineralisation in this area. Further drilling may be required to better define the full extent of any nickel-copper sulphide mineralisation.

Geophysical software is limited in the modelling of EM data (including DHEM data) to a rectangular or square shape, and does not provide details of the geometry of a conductive source. DHEM surveys will, however, continue to be a critical tool in guiding exploration in this complex area.

Plate Name	x	y	z	Dip	Dip Direction	Rotation	Length	Depth Extent	Conductivity-Thickness (S)
MAD116:X1	231443.4	6806514	237	1	11	0	16	17	208651
MAD116:X2	231446.1	6806499	246	-21	109	0	18	8	188426
MAD116:XXX	231449.9	6806506	238	67	90	66	12	8	250000
MAD120b:X1	231455	6806521	239	12	242	0	10	34	210400

Table 1 – modelled parameters of the new DHEM plates

DRILL PROGRAMME

Table 1 contains details of the initial drill holes for the current programme at Mt Alexander.

Drill hole MAD122 is currently being drilled, and is a step-out 50m to the west of the massive nickel-copper sulphides intersected in MAD60 which returned assays of 5.3m @ 4.95%Ni, 2.75%Cu, 0.16%Co, and 4.55g/t total PGEs from 157.9m.

MAD121 was completed on Monday this week to a downhole depth of 319m. The hole is a 120m step-out from MAD120b, and was designed to test continuity of the mineralised ultramafic in the north-west plunge direction. The drill hole intersected a mafic unit between 255.78m to 256.80m with low values of nickel and chrome. No sulphides were observed. The remainder of the drill hole intersected granites.

MAD119 was completed last week to a downhole depth of 350m. The hole is a 150m step-out to the north of MAD114 on the MAD60 section. The drill hole intersected a mafic unit between 242.8m to 245.41m with minor sulphides, and another mafic unit between 250.1m to 254.1m with no observed sulphides. The remainder of the drill hole intersected granites.

Both MAD119 and MAD121 intersected a mafic unit in the position predicted by the interpreted down plunge of the mineralised Investigators ultramafic unit. This is encouraging, and a DHEM survey will be carried out in the holes shortly to investigate for the potential of conductive material around each hole.

DHEM surveys will also be carried out in all other drill holes completed in this drill programme.

Hole ID	GDA94_51 East	GDA94_51 North	Hole Depth (m)	Dip	Azi	Target Depth (m)	Target
MAD108	231218	6806453	250	-76	33	205	Test MAD98: X1 plate
MAD109	231422	6806421	160	-80	73	135	Test MAD100:X3 plate
MAD110	231422	6806421	170	-77	338	155	Test MAD100:X2 plate
MAD111	231482	6806487	210	-81	210	185	Test MAD100: X1 plate
MAD112	232000	6806555	140	-58	174	110	Test MAD101: X1 plate
MAD113	233696	6807050	200	-70	185	180	Test MAD102: X1 plate
MAD114	231218	6806453	250	-78	30	205	Test MAD108 plate
MAD115	230784	6806322	150	-68	290	110	Test west of \$M in MAD37/34
MAD116	231482	6806487	240	-76	315	190	Test MAD111:X1 plate
MAD117	232000	6806555	140	-60	180	110	Test MAD112 Plate
MAD118	231482	6806487	220	-78	301	190	Test MAD111:X1 plate
MAD119	231200	6806700	350	-75	180	280	Deep step-out MAD60 Section
MAD120b	231450	6806570	240	-80	185	190	MAD111:X1 plate - north dip extent
MAD121	231400	6806700	320	-75	180	260	Deep step-out MAD111 Section
MAD122	231175	6806450	200	-75	180	160	Test 50 west of MAD60 \$M

Table 2 – planned and completed drill holes for current drill programme at Mt Alexander. Additional drill holes will be added to this programme as results are reviewed.

About the Mt Alexander Project:

The Mt Alexander Project is located 120km south-southwest of the Agnew-Wiluna Belt, which hosts numerous world-class nickel deposits. The Project comprises five granted exploration licences – E29/638, E29/548, E29/962, E29/954 and E29/972.

The Cathedrals, Stricklands and Investigators nickel-copper-cobalt-PGE discoveries are located on E29/638, which is held in joint venture by St George Mining Limited (75%) and Western Areas Limited (25%). St George is the Manager of the Project, with Western Areas retaining a 25% non-contributing interest in the Project (in regard to E29/638 only) until there is a decision to mine.

For further information, please contact:

John Prineas

Executive Chairman

St George Mining Limited

+61 (0) 411 421 253

John.prineas@stgm.com.au

Peter Klinger

Media and Investor Relations

Cannings Purple

+61 (0) 411 251 540

pklinger@canningspurple.com.au

Competent Person Statement:

The information in this report that relates to Exploration Targets, Exploration Results, Mineral Resources or Ore Reserves is based on information compiled by Mr Benjamin Pollard, a Competent Person who is a Member of The Australasian Institute of Mining and Metallurgy. Mr Pollard is a director of Cadre Geology and Mining Pty Ltd which has been retained by St George Mining Limited to provide technical advice on mineral projects.

Mr Pollard has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Pollard consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The following sections are provided for compliance with requirements for the reporting of exploration results under the JORC Code, 2012 Edition.

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc.). These examples should not be taken as limiting the broad meaning of sampling.</i>	The sections of the core that are selected for assaying are marked up and then recorded on a sample sheet for cutting and sampling at the certified assay laboratory. Samples of HQ or NQ2 core are cut just to the right of the orientation line where available using a diamond core saw, with half core sampled lengthways for assay.
	<i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i>	Wherever possible the same side of the drill core is sampled to ensure sample is representative. Appropriate QAQC samples are inserted into the sequences as per industry best practice.
	<i>Aspects of the determination of mineralisation that are Material to the Public Report.</i> <i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i>	Diamond core (both HQ and NQ2) is half-core sampled to geological boundaries no more than 1.5m and no less than 10cm. Samples less than 3kg are crushed to 10mm, dried and then pulverised to 75µm. Samples greater than 3kg are first crushed to 10mm then finely crushed to 3mm and input into the rotary splitters to produce a consistent output weight for pulverisation. Pulverisation produces a 40g charge for fire assay. Elements determined from fire assay are gold (Au), platinum (Pt) and palladium (Pd) with a 1ppb detection limit. To determine other PGE concentrations (Rh, Ru, Os, Ir) a 25g charge for nickel sulphide collect fire assay is used with a 1ppb detection limit. Other elements will be analysed using an acid digest and an ICP finish. These elements are: Ag, Al, As, Bi, Ca, Cd, Co, Cr, Fe, K, Li, Mg, Mn, Mo, Nb, Ni, P, Pb, S, Sb, Sn, Te, Ti, V, W, Zn. The sample is digested with nitric, hydrochloric, hydrofluoric and perchloric acids to effect as near to total solubility of the sample as possible. The sample is then analysed using ICP-AES or ICP-MS. LOI (Loss on Ignition) will be completed on selected samples to determine the percentage of volatiles released during heating of samples to 1000°C.
Drilling techniques	<i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i>	Diamond drilling is completed using HQ sized coring equipment through the weathered zone (mostly saprock) with 3m barrels, and then HQ or NQ2 in fresh rock with 3m or 6m barrels as required. The core is oriented using ACT II electric core orientation.
Drill sample recovery	<i>Method of recording and assessing core and chip sample recoveries and results assessed.</i>	Diamond core recoveries are recorded during drilling and reconciled during the core processing and geological logging. The core length recovered is measured for each run and recorded which is used to calculate core recovery as a percentage.
	<i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i>	Measures taken to maximise core recovery include using appropriate core diameter and shorter barrel length through the weathered zone, which at Cathedrals and Investigators is mostly <20m and Stricklands <40m depth. Primary locations for core loss in fresh rock are on geological contacts and structural zones, and drill techniques are adjusted accordingly, and if possible these zones are predicted from the geological modelling.

Criteria	JORC Code explanation	Commentary
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	No sample recovery issues have yet been identified that would impact on potential sample bias in the competent fresh rocks that host the mineralised sulphide intervals.
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	Geological logging is completed for all drill holes with lithology, alteration, mineralisation, structure and veining recorded. The logging is recorded digitally and imported in the St George Mining central database.
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography.</i>	Logging is both qualitative and quantitative depending on the field being captured. Core is photographed with one tray per photo and stored digitally.
	<i>The total length and percentage of the relevant intersections logged.</i>	All drill holes are geologically logged in full.
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	The HQ and NQ2 core is cut in half length ways just to the right of the orientation line where available using a diamond core saw. All samples are collected from the same side of the core where practicable.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	Reverse circulation holes have been rotary cone split, and wetness recorded during drilling.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	The entire sample is pulverised to 75µm using LM5 pulverising mills. Samples are dried, crushed and pulverized to produce a homogenous representative sub-sample for analysis. A grind quality target of 90% passing 75µm is used.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	Quality control procedures include submission of Certified Reference Materials (standards), duplicates and blanks with each sample batch. QAQC results are routinely reviewed to identify and resolve any issues.
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	Duplicate samples are selected during sampling. Samples comprise two quarter core samples, or for RC comprise a one meter sample equally split into two bags and taken at set meter intervals.
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	The sample sizes are considered to be appropriate for base metal sulphide mineralisation and associated geology.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	Diamond core samples are analysed for Au, Pt and Pd using a 40g lead collection fire assay; for Rh, Ru, Os, Ir using a 25g nickel sulphide collection fire assay; and for Ag, Al, As, Bi, Ca, Cd, Co, Cr, Fe, K, Li, Mg, Mn, Mo, Nb, Ni, P, Pb, S, Sb, Sn, Te, Ti, V, W, Zn using a four acid digest and ICP-AES or MS finish. The assay method and detection limits are appropriate for analysis of the elements required.
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i>	A handheld XRF instrument (Olympus Innov-X Spectrum Analyser) is used to systematically analyse the drill core and RC sample piles onsite. One reading is taken per meter, however for any core samples with matrix or massive sulphide mineralisation then multiple samples are taken at set intervals per meter. The instruments are serviced and calibrated at least once a year. Field calibration of the XRF instrument using standards is periodically performed (usually daily). The handheld XRF results are only used for preliminary assessment and reporting of element compositions, prior to the receipt of assay results from the certified laboratory.

Criteria	JORC Code explanation	Commentary
	<i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</i>	Laboratory QAQC involves the use of internal lab standards using certified reference material (CRMs), blanks and pulp duplicates as part of in house procedures. The Company also submits a suite of CRMs, blanks and selects appropriate samples for duplicates. Sample preparation checks for fineness are performed by the laboratory to ensure the grind size of 90% passing 75µm is being attained.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Significant intersections are verified by the Exploration Manager of St George Mining.
	<i>The use of twinned holes.</i>	No twin holes are currently planned for the upcoming drill program.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	Primary data is captured onto a laptop using acQuire software and includes geological logging, sample data and QA/QC information. This data, together with the assay data, is entered into the St George Mining central SQL database which is managed by external consultants.
	<i>Discuss any adjustment to assay data.</i>	No adjustments or calibrations will be made to any primary assay data reported.
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	Drill holes have been located and pegged using a DGPS system with an expected accuracy of +/-0.05mmm for easting, northing and elevation. Downhole surveys are conducted using a single shot camera approximately every 30m during drilling to record and monitor deviations of the hole from the planned dip and azimuth. Post-drilling downhole gyroscopic surveys will be conducted, which provide more accurate survey results.
	<i>Specification of the grid system used.</i>	The grid system used at the Mt Alexander project is GDA94 (MGA), zone 51.
	<i>Quality and adequacy of topographic control.</i>	Elevation data has been acquired using DGPS surveying at individual collar locations and entered into the central database. A topographic surface has been created using this elevation data.
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	The diamond drill program is testing modelled EM conductors and geological criteria for massive nickel-copper-PGE sulphide mineralisation. The spacing and distribution of the planned drill holes is appropriate to test the defined targets.
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	The completed drilling at Cathedrals, Stricklands and Investigators is not sufficient to establish the degree of geological and grade continuity to support the definition of Mineral Resource and Reserves and the classifications applied under the 2012 JORC code.
	<i>Whether sample compositing has been applied.</i>	No compositing has been applied to the exploration results.
Orientation of data in relation to geological structure	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	Drill holes are planned as perpendicular as possible to the target EM plates and geological units to approximate true width. Most of the ultramafic units in the Cathedrals Belt dip shallow to the north (and occasionally south) and where possible drill holes are planned to intersect perpendicular to this dip. The orientation of key structures may be locally variable.

Criteria	JORC Code explanation	Commentary
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	No orientation based sampling bias has been identified in the data to date.
Sample security	<i>The measures taken to ensure sample security.</i>	Chain of custody is managed by St George Mining. Core samples are stored in the secure facilities at Bureau Veritas laboratory in Perth. Transportation of core is managed by St George contractors and Bureau Veritas and actively track monitored.
Audits or reviews	<i>The results of any audits or reviews of sampling techniques and data.</i>	No audits or reviews have been conducted at this stage.

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral Tenement and Land Status	<i>Type, name/reference number, location and ownership including agreements or material issues with third parties including joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i> <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i>	The Mt Alexander Project is comprised of five granted Exploration Licences (E29/638, E29/548, E29/954, E29/962 and E29/972). Tenement E29/638 is held in Joint Venture between St George (75% interest) and Western Areas (25% interest). E29/638 and E29/548 are also subject to a royalty in favour of a third party that is outlined in the ASX Release dated 17 December 2015 (as regards E29/638) and the ASX release dated 18 September 2015 (as regards E29/548). No environmentally sensitive sites have been identified on the tenements. A registered Heritage site known as Willsmore 1 (DAA identification 3087) straddles tenements E29/548 and E29/638. All four tenements are in good standing with no known impediments..
Exploration Done by Other Parties	<i>Acknowledgment and appraisal of exploration by other parties.</i>	Exploration on tenements E29/638 and E29/962 has been largely for komatiite-hosted nickel sulphides in the Mt Alexander Greenstone Belt. Exploration in the northern section of E29/638 (Cathedrals Belt) and also limited exploration on E29/548 has been for komatiite-hosted Ni-Cu sulphides in granite terrane. No historic exploration has been identified on E29/954 or E29/972. High grade nickel-copper-PGE sulphides were discovered at the Mt Alexander Project in 2008. Drilling was completed to test co-incident electromagnetic (EM) and magnetic anomalies associated with nickel-PGE enriched gossans in the northern section of current tenement E29/638. The drilling identified high grade nickel-copper mineralisation in granite-hosted ultramafic units and the discovery was named the Cathedrals Prospect.
Geology	<i>Deposit type, geological setting and style of mineralisation</i>	The Mt Alexander Project is at the northern end of a western bifurcation of the Mt Ida Greenstones. The greenstones are bound to the west by the Ida Fault, a significant Craton-scale structure that marks the boundary between the Kalgoorlie Terrane (and Eastern Goldfields Superterrane) to the east and the Youanmi Terrane to the west. The Mt Alexander Project is prospective for further high-grade komatiite-hosted nickel-copper-PGE mineralisation (both greenstone and granite hosted) and also precious metal mineralisation (i.e. orogenic gold) that is typified elsewhere in the Yilgarn Craton.
Drill hole information	<i>A summary of all information material to the understanding of the exploration results including tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> • Easting and northing of the drill hole collar • Elevation or RL (Reduced Level – elevation above sea level in meters) of the drill hole collar 	Drill hole collar locations are shown in the maps and tables included in the body of the relevant ASX release.

Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> • Dip and azimuth of the hole • Down hole length and interception depth • Hole length 	
Data aggregation methods	<i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</i>	<p>Reported assay intersections are length and density weighted. Significant intersections are determined using both qualitative (i.e. geological logging) and quantitative (i.e. lower cut-off) methods.</p> <p>For massive sulphide intersections, the nominal lower cut-off is 2% for either nickel or copper. For disseminated, blebby and matrix sulphide intersections the nominal lower cut-off for nickel is 0.3%.</p>
	<i>Where aggregated intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i>	<p>Any high-grade sulphide intervals internal to broader zones of sulphide mineralisation are reported as <i>included</i> intervals.</p> <p>Any disseminated, matrix, brecciated or stringer sulphides with (usually) >1% nickel or copper on contact with massive sulphide mineralisation are grouped with the massive sulphides for calculating significant intersections and the massive sulphide mineralisation is reported as an <i>including</i> intersection.</p>
	<i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i>	No metal equivalent values have yet been used for reporting exploration results.
Relationship between mineralisation widths and intercept lengths	<p><i>These relationships are particularly important in the reporting of exploration results.</i></p> <p><i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. down hole length, true width not known).</i></p>	Assay intersections are reported as down hole lengths. Drill holes are planned as perpendicular as possible to intersect the target EM plates and geological targets so downhole lengths are usually interpreted to be near true width.
Diagrams	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plane view of drill hole collar locations and appropriate sectional views.</i>	A prospect location map, cross section and long section are shown in the body of relevant ASX Releases.
Balanced Reporting	<i>Where comprehensive reporting of all Exploration Results is not practical, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting Exploration Results.</i>	The exploration results reported are representative of the mineralisation style with grades and/or widths reported in a consistent manner.
Other substantive exploration data	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observation; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	<p>All material or meaningful data collected has been reported.</p> <p>Appendix A contains details of significant intersections at the Investigators Prospect announced by the Company.</p>
Further Work	<p><i>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large – scale step – out drilling).</i></p> <p><i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i></p>	Further exploration in the Cathedrals Belt is currently being planned based on results from the recent drill program. Further exploration is also warranted north of the Cathedrals Belt on E29/548, and also in the Mt Alexander greenstone belt to the south.

Hole ID	GDA94 East	GDA94 North	Dip	Azimuth	Depth (m)	From (m)	To (m)	Width (m)	Ni%	Cu%	Co%	Total PGEs g/t	Au g/t	Ag g/t
MAD29	231559.5	6806419.6	-60	160	201.6	104.00	105	1	0.36	0.18	0.01	1.02	0.12	1.50
MAD31	231559.4	6806416.5	-63	133	160	108.00	111.67	3.67	0.56	0.28	0.02	1.22	0.16	1.98
MAD31						111.67	113.24	1.57	6.26	2.71	0.18	4.91	0.19	8.10
<i>Including</i>						112.08	113.09	1.01	7.98	3.13	0.22	5.90	0.14	9.06
MAD32	232040.2	6806403	-73	220	92.7	44	51.6	7.6	0.44	0.19	0.02	0.59	0.03	0.88
MAD32						51.6	53.52	1.92	4.58	1.52	0.14	3.83	0.12	4.43
<i>Including</i>						52.75	53.52	0.77	7.82	2.50	0.24	6.31	0.13	6.82
MAD33	232038.2	6806412	-57	330	129.7	87.45	96.48	9.03	0.43	0.14	0.02	0.44	0.03	1.08
MAD33						96.48	97.49	1.01	5.81	2.33	0.22	4.32	0.12	7.30
MAD34	230769	6806330	-70	25	152.5	94	96.1	2.1	0.52	0.25	0.02	0.57	0.07	2.04
MAD34						96.1	98.89	2.79	1.63	0.53	0.05	1.24	0.11	3.62
<i>Including</i>						98.7	98.89	0.19	7.34	1.53	0.22	3.27	0.05	24.00
MAD37	230772.7	6806327	-84	335	156	110	122	12	0.41	0.13	0.02	0.35	0.04	1.22
MAD37						122	123.27	1.27	5.63	2.16	0.17	3.86	0.10	6.83
<i>Including</i>						122.55	123.27	0.72	7.93	2.75	0.23	4.81	0.07	9.00
<i>And, Including</i>						123.27	123.6	0.33	0.81	0.69	0.03	2.33	0.14	2.50
MAD38	231205.1	6806248	-70	90	65.5	25.4	28.14	2.74	3.77	1.48	0.10	3.85	0.17	5.49
<i>Including</i>						26.3	26.4	0.1	12.80	5.54	0.25	11.52	0.38	36.50
<i>And, Including</i>						27.6	28.14	0.54	8.59	3.43	0.24	6.73	0.14	10.00
MAD40	231575.7	6806427	-68	160	142.3	105.35	106.79	1.44	0.46	0.16	0.02	0.60	0.07	1.32
MAD40						106.79	108.75	1.96	5.09	2.11	0.16	3.46	0.39	6.04
<i>Including</i>						107.75	108.75	1	7.88	3.11	0.24	5.04	0.53	8.00
MAD43	231528.9	6806508	-70	160	180	149.7	157.22	7.52	0.43	0.20	0.02	0.55	0.05	1.13
MAD43						157.22	157.9	0.68	7.09	2.73	0.23	3.54	0.14	9.50
MAD43						170.43	170.53	0.1	4.25	0.98	0.13	2.91	0.11	6.00
MAD43						171.1	171.25	0.15	1.88	1.27	0.06	1.65	0.11	6.50
MAD44	231482.4	6806488	-70	180	180	155.66	156.11	0.45	5.59	1.27	0.18	4.28	0.24	11.70
<i>Including</i>						155.84	156.11	0.27	8.49	1.67	0.27	5.24	0.20	16.50
MAD45	231004.9	6806368	-81	355	229	174	178.23	4.23	0.39	0.13	0.02	0.35	0.04	0.85
MAD45						178.23	180.14	1.91	3.60	1.04	0.11	2.56	0.19	2.71
<i>Including</i>						178.87	179.08	0.21	5.44	0.51	0.17	2.55	0.09	2.50
<i>And, Including</i>						179.76	180.14	0.38	7.10	2.84	0.21	5.42	0.21	7.00
MAD47	231659.8	6806394	-70	175	142.1	42.2	43	0.8	1.77	2.85	0.05	4.31	0.21	8.34
<i>Including</i>						42.2	42.35	0.15	0.92	6.85	0.02	5.35	0.24	21.00
<i>And, Including</i>						42.9	43	0.1	7.54	7.02	0.28	10.04	0.33	14.00
MAD47	231659.8	6806394	-70	175	142.1	43.95	44.2	0.25	1.65	0.74	0.03	2.71	0.13	2.50
MAD48	231559.7	6806410	-70	181	127.1	89.35	91.98	2.63	0.58	0.33	0.02	0.97	0.10	4.36
MAD48						91.98	92.89	0.91	7.23	2.42	0.20	4.51	0.18	8.00
MAD60	231225.2	6806451	-70	178	190	156	157.9	1.9	0.60	0.28	0.02	1.49	0.29	2.63
MAD60						157.9	163.2	5.3	4.95	2.75	0.16	4.55	0.25	8.95
<i>Including</i>						159.38	162.38	3	6.40	3.55	0.21	5.25	0.17	12.18
<i>And, Including</i>						162.9	163.2	0.3	5.93	3.54	0.20	4.36	0.12	11.00
MAD61	231249.4	6806423	-70	180	160.1	133	135.6	2.6	0.37	0.17	0.01	0.48	0.04	0.65
MAD61						135.94	136.18	0.24	0.73	0.61	0.02	1.64	0.14	2.50

MAD62	231587.4	6806445	-70	0	220	195.84	197.25	1.41	0.82	0.31	0.04	0.92	0.07	1.28
MAD62						197.25	197.56	0.31	6.07	2.81	0.23	2.94	0.03	6.50
MAD63	230796.9	6806312	-75	355	128.1	106	110.33	4.33	0.81	0.35	0.03	1.26	0.17	2.66
MAD63						110.33	110.62	0.29	7.73	2.57	0.24	3.26	0.04	5.50
MAD63						110.62	110.77	0.15	0.82	1.05	0.03	6.13	0.08	3.50
MAD72	231242.1	6806418	-75	180	154.7	131.3	135.79	4.49	0.38	0.09	0.02	0.28	0.02	0.55
MAD72						135.79	136	0.21	5.90	0.32	0.19	1.08	0.01	3.00
MAD72						136	136.71	0.71	0.53	0.15	0.02	0.40	0.03	7.00
MAD72						136.71	136.96	0.25	6.23	7.48	0.21	2.52	0.01	18.00

Appendix A - Significant Intersections at the Investigators Prospect